

## SPECIFICATIONS – No. 1187 Stationary 10-Battery Rack

- Width: 25-1/2"
- Depth: 20" (at floor)
- Height: 37-1/4" to top of frame; 50" to top of optional sign.
- Tubing: 3/4" OD x 18 gauge welded steel.
- Shelves: 20 gauge cold rolled steel, double flanged all around; optional 24 gauge steel label track can be ordered for attachment on one or both faces of each shelf (will accommodate 2" labels or 2" x 24" label strips). All shelves 24" wide; top shelf is 9" deep, middle shelf is 14" deep, bottom shelf is 17-1/2" deep.
- X-Brace: 3/4" x 12 gauge steel, attached between two lower shelves for maximum rigidity.
- Fasteners: Bright zinc plated; nuts are hardened spring-prong type. Self-tapping screws are supplied for attachment of label tracks.
- Finish: Baked enamel, after thorough cleaning and phosphatizing. Frame is gloss white, shelves are gloss black.
- Sign (optional): 20 gauge cold rolled steel, 7-1/2" x 24-1/2" (copy area is limited to 6-3/4" x 21-1/2"). Cleaned and phosphatized before finishing. Base color, screened copy, and clear top coat are all baked for durable long-lasting finish. Base color white with copy color(s) as specified. Copy applied both sides unless otherwise specified.
- NOTE: Please request quotation on signs, giving information about colors, copy required, and quantity. Customer is expected to supply artwork or copy layout, either full size or proportionate, suitable for photo reproduction without cleanup.
- Sign Mounting Pins: No. 3 steel wire, bright zinc plated.
- Packaging: Individually cartoned, KD, with illustrated assembly instruction sheet included. Shipping weight 22# (add 4# for set of six label tracks and 2# for sign and sign pins (if included). Exterior carton size: 42" x 24-3/4" x 2-3/4". Package qualifies for shipment by United Parcel Service.
- Availability: Basic rack and label tracks available from stock – no specific quantity purchase commitment required except for signs where required.